



# Intel® Ethernet SFP+ Twinaxial Cables

SFP+ Direct Attach cables for the Intel® Ethernet Converged Network Adapter X520 Family



## Features

- 1 m (3.3 ft.), 3 m (9.8 ft.), and 5 m (16.4 ft.) SFP+ 10 GbE direct attach passive copper cables
- SFP+ Direct Attach cables offer a highly cost-effective way to connect within racks and across adjacent racks
- Fully compatible with the Intel® Ethernet Converged Network Adapter X520 Family
- Zinc die-cast SFF-8431 SFP+ connectors
- Low cross-talk and pair-to-pair skew
- Fully compliant to the latest SFP Plus MSA (multi-source agreement)
- Data rates backward compatible to 1 Gbps
- Reduced power budget and lower port cost compared to optical solutions
- Conforms to environmental standards as described in the *Product Environmental Content Report*<sup>1</sup>
- One year warranty

The Intel® Ethernet Converged Network Adapter X520 family with SFP+ connectivity delivers the most flexible and scalable Ethernet adapters for today's demanding data center environments. The escalating deployments of multi-core processor-based servers and demanding applications such as server virtualization, High Performance Computing (HPC), unified storage deployments, and video-on-demand are driving the need for 10 Gigabit connections. Customers require flexible and scalable I/O solutions to meet the rigorous requirements of these deployments.

Powered by Intel's third-generation 10 GbE network controller, the Intel® Ethernet 82599 10 Gigabit Ethernet Controller, the X520 server adapter family addresses the demanding needs of the next-generation data center by providing unmatched features for virtualization, flexibility for LAN and SAN networking, and proven, reliable performance.

To ensure maximum flexibility, Intel uniquely supports the ability to mix any combination of SFP+ optical modules, direct attach copper cables, or 1000BASE-T SFP modules on the Intel Ethernet X520 Adapters. For instance, customers can remove the optical modules that come installed on the adapter and replace them with an Intel® Ethernet SFP+ Optic, an Intel® Ethernet SFP+ Twinaxial Cable, or a 1000BASE-T SFP module. Intel® Ethernet SFP+ Twinaxial Cables are ideal for short distances and offer a highly cost-effective way to connect within racks and across adjacent racks. The cables are available in three lengths; 1, 3, and 5 meters, enabling customers to create the configuration that best meets the needs of their data center environment.

Note: Other manufacturers may require specific cables for equipment compatibility. Please check with the manufacturer of your device regarding cable requirements for that device.

## Intel® Ethernet SFP+ Twinaxial Cables Product Codes

XDACBL1M (1 meter)

XDACBL3M (3 meter)

XDACBL5M (5 meter)

## Intel® Ethernet SFP+ Optics Product Codes

E10GSFSPR—Intel® Ethernet SFP+ SR Optic

E10GSFPLR—Intel® Ethernet SFP+ LR Optic

## Compatible Intel® Server Adapters Product Codes

E10G42BTDA—Intel® Converged Network Adapter X520-DA2

E10G41BFSR—Intel® Converged Network Adapter X520-SR1\*

E10G42BFSR—Intel® Converged Network Adapter X520-SR2\*

E10G41BFLR—Intel® Converged Network Adapter X520-LR1\*

\* Ships with pluggable optic installed

Electrical/Cable Characteristics					
Parameter	Symbol	Min	Typ	Max	Unit
Storage Temperature Range	$T_S$	-40	--	85	°C
Operating Temperature Range	$T_A$	-40		85	°C
Operating Humidity Range	RH	0		85	%
Supply Voltage	Vcc	2.95	3.3	3.6	V
Supply Current (per cable end)	Icc	--	100	--	μA
Power Consumption		--	0.4	--	mW
Data Rate	DR	--	--	11.3	Gbps
<b>Transmitter</b>					
Differential Input Voltage Swing	$V_{DIFF}$	300	--		mVp-p
Differential Input Return Loss	SDD11		-10		dB @ 5 GHz
<b>Receiver</b>					
Differential Output Return Loss	SDD22		-10		dB @ 5 GHz
Voltage Modulate Amplitude Loss	L			4.5	dBe
VMA Loss to Crosstalk Ratio	VCR	32.5			dB
Waveform Dispersion Penalty	dWDP			6.8	dBe
<b>Cable</b>					
Cable Differential Impedance			100	105	Ω
Cable Outer Diameter			0.175 <sup>30AWG</sup> 0.235 <sup>24AWG</sup>		Inches
Cable Bend Radius (Measured at Diecast Endface)			0.7 <sup>30AWG</sup> 0.95 <sup>24AWG</sup>		Inches
Cable Flex Cycle			200		cycles
Cable Weight			30 <sup>30AWG</sup> 50 <sup>24AWG</sup>		kg/km

Length and Part Number		
SKU	Length	AWG
XDACBL1M	1000 mm ± 25 mm	30
XDACBL3M	3000 mm ± 75 mm	30
XDACBL5M	5000 ± 125 mm	24

Difference Waveform Dispersion Penalty			
Cable	WDPI	WDPO	dWDP
1 m, 30AWG	2.0965	4.2087	2.1122
3 m, 30AWG	2.0965	6.6828	4.5863
5 m, 24AWG	2.0965	6.2477	4.1512

Note: dWDP=6.8 (max), SFF-8431

Voltage Modulation Amplitude to Crosstalk Ratio (VCR)					
Cable	B' VMA (mV)	C' VMA (mV)	VMA LOSS (dB)	NEXT (rms) (mV)	VCR (dB)
1 m, 30AWG	700	615	1.12	1.73	35.8
3 m, 30AWG	700	503	2.86	1.79	34.4
5 m, 24AWG	700	505	2.84	1.87	34.0

Notes: VMA LOSS (dB)=4.5 (max), SFF-843. VCR=32.5 dB (min), SFF-8431

## Customer Support

Intel® Customer Support Services offers a broad selection of programs including phone support and warranty service. For more information, contact us at:

[support.intel.com/support/go/network/](http://support.intel.com/support/go/network/)

(Service and availability varies by country.)

## For Product Information

To speak to a customer service representative regarding Intel products, call 1-800-538-3373 (U.S. and Canada) or visit:

[support.intel.com/support/go/network/contact.htm](http://support.intel.com/support/go/network/contact.htm)

For more information on the Intel® Ethernet SFP+ Twinaxial Cables visit: [www.intel.com/go/ethernet](http://www.intel.com/go/ethernet)

<sup>1</sup> Product Environmental Content Reports are found on Intel Web site at <http://qdms.intel.com>.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY INTEL, THE INTEL PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE INTEL PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request. Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order. Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or by visiting Intel's Web Site at <http://www.intel.com>.

Copyright © 2011 Intel Corporation. All rights reserved. Intel, the Intel logo, and Xeon are trademarks of Intel Corporation in the U.S. and other countries.

\*Other names and brands may be claimed as the property of others.

